



Clean up your rack and organize your power connections with the Datacom Systems Multi-Unit Power Supply.

This easy to manage 1U power supply contains two (2) redundant hot-swappable power supplies and contains 24 lead power connections to provide dual redundant power for up to 12 Datacom Systems network taps, SINGLEstream™ link aggregation taps, or VERSAstream™ aggregators. Each power lead connector delivers up to 3 amps.

Includes AC power cords and cabling to power up to 12 redundant devices located within 5U of the power supply.

- Powers up to 12 redundant power connections
- Easy to connect with included cabling set
- Universal power for global deployment
- Fits a standard 19" rack mount
- LEDs on hot-swappable power supplies confirm power status
- Fully RoHS compliant

TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Connectors | |
| 24 - 5.0 VDC 3.0 A Receptacles | |
| Power Consumption Watts | |
| 480.0 | |
| BTU/h | |
| 1636.8 | |
| Electrical Specifications | |
| Input: 100-240VAC, 50-60 Hz, 0.4A-0.2A | |
| Certifications | |
| CE | |
| Physical Dimensions (HxWxD) | |
| 1.75 x 19.00 x 13.00 in (4.45 x 48.26 x 33.02 cm) | |
| Weight | |
| 10.0 lbs (4.54 kgs) | |
| Environment | |
| Operating Temperature: 32° to 104°F (0° to 40°C) | |
| Storage Temperature: -22° to 149°F (-30° to 65°C) | |
| Humidity: 5 to 90% non-condensing | |
| Warranty | |
| Two (2) Year Limited Warranty | |
| Order Information | |
| Product | Description |
| RPS-12-5-AC | Dual Redundant Rack Mountable AC Power Supply |

ACCESS YOUR NETWORK™