



AGGREGATION

The SINGLEstream™ 1214LX-10Gb can combine data from up to five single mode Gigabit network segments into one or more streams of data. Connected 10 Gigabit monitoring devices can receive aggregated data from multiple network segments with just one network interface card (NIC) each. Any of the configurable 10 Gigabit Ports can also be set to receive data from SPAN ports.

REGENERATION

With a total of four (4) configurable ports the SS-1214LX-10Gb can be configured to have multiple monitoring ports to allow connected devices to receive multiple copies of the same data stream. Allowing multiple monitoring and analysis devices to collect data from the same network segments at the same time eliminates contention for SPAN ports.

PORT STEERING

The Any-to-Any port architecture of the SS-1214LX-10Gb allows you to send traffic from any network port to any monitoring port eliminating the need for network personnel to manage or change complex configurations of SPAN ports or move tools around their network.

- 24X7 access point for network monitoring and security tools
- Passive taps are 100% fault tolerant and won't break the link even if power is lost to the device
- "Any-to-Any" architecture can send traffic from any network port to any monitoring port, while XFP ports can be configured as monitoring ports or accept input from SPAN
- "Many-to-Any" architecture combines traffic from multiple ports, providing visibility into multiple network connections
- "One-to-Many" architecture allows you to send multiple copies of data from the input port to multiple monitoring devices
- Hot swappable dual redundant load balanced power supplies
- Hot swappable management card compatible with filtering

TECHNICAL SPECIFICATIONS

Connectors

Network Ports: Five (5) Taps w/ Quad LC Connectors [9 micron]
 Any-to-Any Ports: Four (4) XFP
 Management Port (rear): RJ45 @ 100Mbps Full-Duplex
 Configuration Port (rear): DB9F Serial Port

Power Requirements

Input: 100-240VAC, 50-60Hz, 0.4-0.2A

Split Ratio

50/50

Insertion Loss

4dB

Certifications

CE

Physical Dimensions (HxWxD)

1.75 x 19.00 x 21.00 in (4.45 x 48.26 x 53.35 cm)

Weight

13.75 lbs (6.24 kgs)

Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)
 Storage Temperature: -22° to 149°F (-30° to 65°C)
 Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
SS-1214LX-10G	SINGLEstream™ Gigabit to 10 Gigabit Link Aggregation Tap (4 - XFP Any-to-Any Ports, 5 LX Network Taps)
XFPs	XFP-SR or XFP-LR (Required Additional Purchase)