


Overview: The RMC (Rack Mount Chassis) units are designed to save rack space by allowing multiple Datacom Systems Taps or Network Packet Brokers into a professional, neat, and orderly chassis. RMC units are often deployed in locations where monitoring solutions require access to copies of network traffic.

Rack mounts are also beneficial to a Data Capture Infrastructure as they allow additional Taps and Network Packet Brokers to be installed as needs change. Rack mounts come in four varieties, depending on the type of device being installed, and the number of devices.



RMC12-2

RMC Compatibility: RMC rack mounts are compatible with all Datacom Systems devices that are not large enough to be rackmounted by themselves.

Refer to the tables below to determine the appropriate rack mount for each unit type:

Models Compatible with RMC-12-2	
FTP-1516	SS-2206BT-BT-S
FTP-4000 Series	SS-2206SX-SFP-S
SS-1204BT-BT-S	SS-2210-BT-BT/SFP-S
SS-1204BT-SFP-S	SS-4210BT-SFP-S
SS-1204LX-BT-S	VS-1204BT-S
SS-1204LX-SFP-S	VS-1208BT-S
SS-1204SX-BT-S	VS-1210BT/SFP-S
SS-1204SX-SFP-S	VS-1210SFP-S

Feature	Specification
Device Capacity	Twelve RMC-2 Taps/Network Packet Borkers
Dimensions:	10.500" (H) x 19.000" (W) x 12.250" (D) (includes rack mount bracket) 267 mm (H) x 483 mm (W) x 311 mm (D)
Weight	Unit - 9 pounds; Shipping - 18 pounds - 4.08 kg; Shipping - 8.16 kg

For More information

Customer Service is available from our website: www.datacomsystems.com or by calling +1 315 463 9541