



# 10/100-AT Ethernet TAP



## Ideal for secure non-intrusive, dedicated access to your network links

The 10/100-AT Ethernet Tap's fault tolerant design will help ensure that network performance and integrity will not be affected by power loss. The 10/100-AT provides a method to observe traffic on a full duplex Ethernet segment. It enable easy access to segments while maintaining network integrity with "no break the link" design. Network performance will not be affected by power loss.

- Permanent In-Line access for monitoring of 10/100 Ethernet links-
- Redundant power supply minimizes risk of power loss
- Ideal for Security and Monitoring applications
- View ALL seven layers of network traffic
- View ALL traffic on both sides of full duplex links
- Rack-mount chassis models available to mount 3 units (1RU) or 14 units (4RU)

## Technical Specifications

### Ports

One (1) 10/100 (RJ45) Network TAP port pair  
Two (2) 10/100 (RJ45) Monitor Ports

### Power Requirements

Two (2) External AC Adapters (included)  
Input: 100-240 VAC, 50-60Hz, 0.8A

### Physical Dimensions (H x W x D)

1.07 x 5 x 5 in. (2.7 x 12.7 x 12.7 cm)

### Weight

8 oz. (0.23 Kg)

### Certifications

CE, ROHS

### Environmental

Operating Temperature: 32° to 104° F (0° to 40° C)  
Storage Temperature: -22° to 149° F (-30° to 65° C)  
Humidity: 5% to 90% non-condensing

### Warranty

One (1) Year Standard Hardware Warranty  
Extended Support available

### ORDERING INFORMATION

Product	Description
10/100 -AT	10/100 Ethernet Tap
TAP RMC-3	3-Unit Rack Mount (shown below)
RMC-12-3	12-Unit Rack Mount